

TAPING SPECIFICATIONS 编带标准

■ For Radial Type Aluminum electrolytic capacitors with non-solid electrolyte 适用于引线式非固体铝电解电容

Lead Code 成型名称及代码	Terminal Type 端子外形图	Dimension 尺寸表																																													
Straight Cut 直脚剪脚 CC (4 ~ 18Φ)		<table border="1"> <tr> <td>φD</td> <td>4</td> <td>5</td> <td>6.3</td> <td>8</td> <td>10</td> <td>13</td> <td>16</td> <td>18</td> </tr> <tr> <td>F</td> <td>1.5</td> <td>2.5</td> <td>2.5</td> <td>3.5</td> <td>5.0</td> <td>5.0</td> <td>7.5</td> <td>7.5</td> </tr> </table>	φD	4	5	6.3	8	10	13	16	18	F	1.5	2.5	2.5	3.5	5.0	5.0	7.5	7.5																											
φD	4	5	6.3	8	10	13	16	18																																							
F	1.5	2.5	2.5	3.5	5.0	5.0	7.5	7.5																																							
Forming Cut 成型剪脚 FC (4 ~ 8Φ)		<table border="1"> <tr> <td>φD</td> <td>4</td> <td>5</td> <td>6.3</td> <td>8</td> </tr> <tr> <td>F</td> <td>2.5</td> <td>2.5</td> <td>5.0</td> <td>5.0</td> </tr> </table>	φD	4	5	6.3	8	F	2.5	2.5	5.0	5.0																																			
φD	4	5	6.3	8																																											
F	2.5	2.5	5.0	5.0																																											
Forming Cut 成型剪脚 CM (4 ~ 5Φ)		<table border="1"> <tr> <td>φD</td> <td>4</td> <td>5</td> </tr> <tr> <td>F</td> <td>2.5</td> <td>2.5</td> </tr> </table>	φD	4	5	F	2.5	2.5																																							
φD	4	5																																													
F	2.5	2.5																																													
Kinked Forming Cut 弯曲成型剪脚 FS (4 ~ 8Φ)		<table border="1"> <tr> <td>φD</td> <td>4</td> <td>5</td> <td>6.3</td> <td>8</td> <td>10</td> <td>13</td> <td>16</td> <td>18</td> </tr> <tr> <td>H</td> <td>5.0</td> <td>5.0</td> <td>5.0</td> <td>5.0</td> <td>4.5</td> <td>4.5</td> <td>4.5</td> <td>4.5</td> </tr> <tr> <td>H1</td> <td>2.8</td> <td>2.8</td> <td>2.8</td> <td>2.8</td> <td>2.5</td> <td>2.5</td> <td>2.5</td> <td>2.5</td> </tr> <tr> <td>E</td> <td colspan="8">1.1</td> </tr> <tr> <td>P</td> <td colspan="4">1.1</td> <td colspan="4">1.2</td> </tr> </table>	φD	4	5	6.3	8	10	13	16	18	H	5.0	5.0	5.0	5.0	4.5	4.5	4.5	4.5	H1	2.8	2.8	2.8	2.8	2.5	2.5	2.5	2.5	E	1.1								P	1.1				1.2			
φD	4	5	6.3	8	10	13	16	18																																							
H	5.0	5.0	5.0	5.0	4.5	4.5	4.5	4.5																																							
H1	2.8	2.8	2.8	2.8	2.5	2.5	2.5	2.5																																							
E	1.1																																														
P	1.1				1.2																																										
Kinked Straight Cut 弯曲直脚剪脚 SC (10 ~ 18Φ)		<table border="1"> <tr> <td>φD</td> <td>4</td> <td>5</td> <td>6.3</td> <td>8</td> <td>10</td> <td>13</td> <td>16</td> <td>18</td> </tr> <tr> <td>H</td> <td>5.0</td> <td>5.0</td> <td>5.0</td> <td>5.0</td> <td>4.5</td> <td>4.5</td> <td>4.5</td> <td>4.5</td> </tr> <tr> <td>H1</td> <td>2.8</td> <td>2.8</td> <td>2.8</td> <td>2.8</td> <td>2.5</td> <td>2.5</td> <td>2.5</td> <td>2.5</td> </tr> <tr> <td>E</td> <td colspan="8">1.1</td> </tr> <tr> <td>P</td> <td colspan="4">1.1</td> <td colspan="4">1.2</td> </tr> </table>	φD	4	5	6.3	8	10	13	16	18	H	5.0	5.0	5.0	5.0	4.5	4.5	4.5	4.5	H1	2.8	2.8	2.8	2.8	2.5	2.5	2.5	2.5	E	1.1								P	1.1				1.2			
φD	4	5	6.3	8	10	13	16	18																																							
H	5.0	5.0	5.0	5.0	4.5	4.5	4.5	4.5																																							
H1	2.8	2.8	2.8	2.8	2.5	2.5	2.5	2.5																																							
E	1.1																																														
P	1.1				1.2																																										
Forming & Bending (Right) 卧式右弯剪脚 BR (13 ~ 18Φ)		<table border="1"> <tr> <td>φD</td> <td>13</td> <td>16</td> <td>18</td> </tr> <tr> <td>F</td> <td>5.0</td> <td>7.5</td> <td>7.5</td> </tr> <tr> <td>H₁</td> <td colspan="3">2.5Max.</td> </tr> </table>	φD	13	16	18	F	5.0	7.5	7.5	H ₁	2.5Max.																																			
φD	13	16	18																																												
F	5.0	7.5	7.5																																												
H ₁	2.5Max.																																														
Forming & Bending (Left) 卧式左弯剪脚 BL (13 ~ 18Φ)		<table border="1"> <tr> <td>φD</td> <td>13</td> <td>16</td> <td>18</td> </tr> <tr> <td>F</td> <td>5.0</td> <td>7.5</td> <td>7.5</td> </tr> <tr> <td>H₁</td> <td colspan="3">2.5Max.</td> </tr> </table>	φD	13	16	18	F	5.0	7.5	7.5	H ₁	2.5Max.																																			
φD	13	16	18																																												
F	5.0	7.5	7.5																																												
H ₁	2.5Max.																																														

Lead diameter and lead pitch are subject to capacitor specifications 引线的直径和脚距请参阅各系列的详细规格。

Note: All design and specifications are for reference only and is subject to change without prior notice. If any doubt about safety for your application, Please contact us immediately for technical assistance before purchase.

注：以上所提供的设计及特性参数仅供参考，任何修改不作预先通知，如有使用上任何疑问，请在采购前与我们联系，以便提供技术上的协助。